



12,5-560 kVA

MODELLO Model Model	POTENZA kVA Power kVA Puissance kVA				MOTORE Engine Moteur Mod.	SERBATOIO Tank Réervoir L	DIMENSIONI Dimensions Dimensions			PESO Weight Poids kg	TIPO Type Genre
	50 Hz		60 Hz				L L L	L W L	A H H		
	CONT	MAX	CONT	MAX			mm	mm	mm		
ALTERNATORE COMPOUND - compound alternator											
FE16 D-O	12,5	13,1	15	15,9	"F2M2011 (OIL) (M)"	6 0	1500	700	1020	455	OPENTYPE
FE16 D-SV						7 0	1750	700	1020	577	SOUNDPROOFVERTICALOPENING
FE16 D-S						7 0	1750	700	1125	610	SOUNDPROOFLATERALDOOR
FE22 D-O	20	22	24	26	"F3M2011 (OIL) (M)"	6 0	1500	700	1020	515	OPENTYPE
FE22 D-SV						7 0	1750	700	1020	620	SOUNDPROOFVERTICALOPENING
FE22 D-S						70	1750	700	1125	740	SOUNDPROOFLATERALDOOR
ALTERNATORE REG ELETTRONICO - AVR alternator											
FE16 D-OA	12,5	13,1	15	15,9	"F2M2011 (OIL) (M)"	6 0	1500	700	1020	497	OPENTYPE
FE16 D-SVA						7 0	1750	700	1020	582	SOUNDPROOFVERTICALOPENING
FE16 D-SA						7 0	1750	700	1125	595	SOUNDPROOFLATERALDOOR
FE22 D-OA	20	22	24	26	"F3M2011 (OIL) (M)"	6 0	1500	700	1020	565	OPENTYPE
FE22 D-SVA						7 0	1750	700	1020	600	SOUNDPROOFVERTICALOPENING
FE22 D-SA						7 0	1750	700	1125	760	SOUNDPROOFLATERALDOOR
FE33 D-O	30	33	35,7	37,5	"F4M 2011 (OIL) (M)"	7 0	1750	700	1125	620	OPENTYPE
FE33 D-SV						70	1750	700	1020	740	SOUNDPROOFVERTICALOPENING
FE33 D-S						100	2100	870	1165	860	SOUNDPROOFLATERALDOOR
FE44 D-O	40	44	48	50	"BF4M 2011 (OIL) (M)"	70	1750	700	1100	695	OPENTYPE
FE44 D-SV						70	1850	700	1020	790	SOUNDPROOFVERTICALOPENING
FE44 D-S						100	2100	870	1165	900	SOUNDPROOFLATERALDOOR
FE66 D-O	60	66	/	/	"BF4M 2011C (OIL) (M)"	100	2100	870	1300	785	OPENTYPE
FE66 D-S					100	2260	1000	1420	1170	SOUNDPROOF	
FE84 D-O	75	81	81	92	"BF4M 2012C (M)"	100	2100	870	1300	1030	OPENTYPE
FE84 D-S					130	2500	1000	1420	1390	SOUNDPROOF	
FE110 D-O	105	112	112	117	"BF4M 1013EC (M)"	100	2100	870	1300	1200	OPENTYPE
FE110 D-S					140	2850	1000	1420	1590	SOUNDPROOF	
FE145 D-O	130	143	135	143	(E)"	125	2500	1000	1400	1280	OPENTYPE
FE145 D-S					150	3000	1100	1520	1810	SOUNDPROOF	
FE165 D-O	150	165	171	180	"BF6M 1013EC (M)"	125	2500	1000	1400	1540	OPENTYPE
FE165 D-S					170	3300	1100	1770	2090	SOUNDPROOF	
FE176 D-O	164	172	171	180	"BF6M1013FCG2 (E)"	125	2500	1000	1400	1580	OPENTYPE
FE176 D-S					170	3300	1100	1770	2130	SOUNDPROOF	
FE198 D-O	180	198	207	232	"BF6M 1013FCG3 (E)"	140	2850	1000	1650	1580	OPENTYPE
FE198 D-S					170	3300	1100	1770	2130	SOUNDPROOF	
FE220 D-O	200	220	226	250	"4V (E)"	140	2850	1000	1650	1700	OPENTYPE
FE220 D-S					170	3300	1100	1770	2250	SOUNDPROOF	
FE280 D-O	250	279	254	286	"BF6M 1015C-G1 (E)"	150	3000	1100	1650	2050	OPENTYPE
FE280 D-SB					195	3800	1200	1940	2900	SOUNDPROOF	
FE330 D-O	300	330	338	374	(E)"	290	3200	1100	2200	2180	OPENTYPE
FE330 D-S					230	3950	1300	2135	3740	SOUNDPROOF	
FE385 D-O	350	385	/	/	(E)"	290	3200	1300	2200	2350	OPENTYPE
FE385 D-S					410	4300	1600	2190	3900	SOUNDPROOF	
FE505 D-O	450	480	464	512		290	3200	1300	2200	2800	OPENTYPE
FE505 D-S					410	4300	1600	2190	4380	SOUNDPROOF	
FE560 D-O	510	560	536	588		290	3200	1300	2200	2870	OPENTYPE
FE560 D-S					410	4300	1600	2190	4850	SOUNDPROOF	