

MODELLO Model Model	POTENZA kVA Power kVA Puissance kVA				MOTORE Engine Moteur	SERBATOIO Tank R�servoir	DIMENSIONI Dimensions Dimensions			PESO Weight Poids	TIPO Type Genre			
	50 Hz		60 Hz				L L L	L W L	A H H					
	CONT	MAX	CONT	MAX			Mod.	L	mm			mm	mm	kg
	ALTERNATORE COMPOUND - compound alternator													
FE22 B1-O	20	22	/	/	4M06G25/5 (E)	70	1750	700	1100	560	OPEN			
FE22 B1-S						100	2100	870	1165	625	SUPER SOUNDPROOF			
FE33 B1-O	30	33	/	/	4M06G35/5 (E)	70	1750	700	1100	720	OPEN			
FE33 B1-S						100	2100	870	1165	940	SUPER SOUNDPROOF			
FE44 B1-O	40	44	/	/	4M06G44/5 (E)	70	1750	700	1100	790	OPEN			
FE44 B1-S						100	2100	870	1165	1005	SUPER SOUNDPROOF			
FE50 B1-O	45	50	/	/	4M06G50/5 (E)	70	1750	700	1100	820	OPEN			
FE50 B1-S						100	2100	870	1165	1020	SUPER SOUNDPROOF			
FE55 B1-O	50	55	/	/	4M06G55/5 (E)	70	1750	700	1100	900	OPEN			
FE55 B1-S						100	2100	870	1165	1150	SUPER SOUNDPROOF			
FE66 B-O	60	66	/	/	4M11G70/5 (E)	100	2260	1000	1500	1100	OPEN			
FE66 B-S						140	2850	1000	1420	1300	SUPER SOUNDPROOF			
FE88 B-O	80	88	/	/	4M11G90/5 (E)	100	2260	1000	1500	1100	OPEN			
FE88 B-S						140	2850	1000	1420	1300	SUPER SOUNDPROOF			
FE110 B-O	100	110	/	/	4M11G120/5 (E)	100	2260	1000	1500	1300	OPEN			
FE110 B-S						140	2850	1000	1420	1650	SUPER SOUNDPROOF			
FE145 B-O	135	150	/	/	6M11G150/5 (E)	125	2500	1000	1400	1400	OPEN			
FE145 B-S						160	3000	1100	1520	1850	SUPER SOUNDPROOF			
FE165 B-O	150	165	/	/	6M11G165/5 (E)	125	2500	1000	1400	1480	OPEN			
FE165 B-S						160	3000	1100	1520	2050	SUPER SOUNDPROOF			
FE220 B-O	200	220	/	/	6M16G220/5 (E)	140	3300	1100	1700	2000	OPEN			
FE220 B-SB						220	3800	1200	1940	2510	SUPER SOUNDPROOF			
FE250 B-O	225	250	/	/	6M16G250/5 (E)	150	3300	1100	1700	2200	OPEN			
FE250 B-SB						220	3800	1200	1940	2600	SUPER SOUNDPROOF			
FE280 B-O	250	275	/	/	6MG16G275/5 (E)	150	3300	1100	1700	2300	OPEN			
FE280 B-SB						220	3800	1200	1940	2700	SUPER SOUNDPROOF			
FE330 B-O	300	330	/	/	6MG16G350/5 (E)	193	3300	1100	1700	2630	OPEN			
FE330 B-SB						220	3800	1200	1940	3630	SUPER SOUNDPROOF			
FE385 B-O	350	385	/	/	6M21G385/5 (E)	193	3200	1300	2100	3400	OPEN			
FE385 B-S						230	3950	1300	2135	3840	SUPER SOUNDPROOF			
FE440 B-O	400	440	/	/	6M21G440/5 (E)	193	3200	1300	2100	3400	OPEN			
FE440 B-S						230	3950	1300	2135	4670	SUPER SOUNDPROOF			
FE505 B1-O	450	500	/	/	6M21G500/5 (E)	193	3200	1300	2200	3430	OPEN			
FE505 B1-S						260	4500	1450	2190	5300	SUPER SOUNDPROOF			
FE560 B-O	500	550	/	/	6M26G550/5 (E)	320	3400	1400	2200	3490	OPEN			
FE560 B-S						310	5000	1900	2295	6000	SUPER SOUNDPROOF			
FE610 B-O	550	605	/	/	6M33G660/5 (E)	320	3400	1400	2200	4000	OPEN			
FE610 B-S						310	5000	1900	2295	6200	SUPER SOUNDPROOF			
FE660 B-O	600	660	/	/	6M33G660/5 (E)	340	3400	1400	2100	4600	OPEN			
FE660 B-S						310	5000	1900	2295	6500	SOUNDPROOF			
FE700 B-O	650	715	/	/	6M33G715/5 (E)	340	3400	1400	2100	4900	OPEN			
FE700 B-S						310	5000	1900	2295	6800	SOUNDPROOF			
FE810 B-O	750	825	/	/	6M33G825/5 (E)	370	3800	1700	2250	6000	OPEN			
FE810 B-SB						350	5850	1900	2350	8000	SOUNDPROOF			
FE880 B-O	800	880	/	/	12M26G900/5 (E)	370	4500	2050	2460	6250	OPEN			
FE880 B-SB						650	6500	2270	2550	8000	SOUNDPROOF			
FE900 B-O	800	900	/	/	12M26G900/5 (E)	370	4500	2050	2460	6500	OPEN			
FE900 B-SB						650	6500	2270	2550	8000	SOUNDPROOF			
FE1000 B-O	900	1000	/	/	12M26G1000/5 (E)	400	4500	2050	2460	7700	OPEN			
FE1000 B-SB						650	6500	2270	2550	11100	SOUNDPROOF			
FE1120 B-O	1000	1100	/	/	12M26G1100/5 (E)	520	4800	2050	2200	7800	OPEN			
FE1120 B-SB						650	6500	2270	2550	11400	SOUNDPROOF			
FE1260 B-O	1125	1250	/	/	12M33G1250/5 (E)	800	5150	2200	2570	11000	OPEN			
FE1260 B-SB						670	7000	2460	3060	11610	SOUNDPROOF			
FE1380 B-O	1250	1400	/	/	12M33G1400/5 (E)	800	5150	2200	2570	11600	OPEN			
FE1380 B-SB						670	7000	2460	3060	13300	SOUNDPROOF			
ALTERNATORE REG ELETTRONICO - AVR alternator														
FE1650 B-O	1500	1700	/	/	6M16G275/5 (E)	800	5200	2200	2500	12000	OPEN TYPE			
FE1650 B-SB						250	8300	2460	3060	14500	SOUNDPROOF			
FE1870 B-O	1750	1900	/	/	6M16G350/5 (E)	800	5200	2220	2660	12400	OPEN TYPE			
FE1870 B-SB						250	8300	2460	3060	18000	SOUNDPROOF			