

MODELLO Model Model	POTENZA kVA Power kVA Puissance kVA				MOTORE Engine Moteur	SERBATOIO Tank Réservoir	DIMENSIONI Dimensions Dimensions			PESO Weight Poids	TIPO Type Genre
	50 Hz		60 Hz				L L L	L W L	A H H		
	CONT	MAX	CONT	MAX			Mod.	L	mm		
FE33 I1-O	30	33	34	37	M80313AM1P (E)	70	1750	700	1100	685	OPEN TYPE
FE33 I1-S						100	2100	870	1165	950	SOUNDPROOF
FE44 I1-O	40	44	/	/	N45AM1A (M)	70	1750	700	1100	765	OPEN TYPE
FE44 I1-S						100	2100	870	1165	960	SOUNDPROOF
FE55 I1-O	50	55	54,4	60	N45AM2 (M)	70	1750	700	1300	810	OPEN TYPE
FE55 I1-S						100	2100	870	1165	1010	SOUNDPROOF
FE66 I1-O	60	66	68	75	N45SM1A (M)	100	2100	870	1300	865	OPEN TYPE
FE66 I1-S						100	2260	1000	1420	1225	SOUNDPROOF
FE84 I1-O	75	83	75	83	N45SM3 (M)	100	2100	900	1300	955	OPEN TYPE
FE84 I1-S						100	2260	1000	1420	1280	SOUNDPROOF
FE88 I1-O	80	88	96	106	N45SM3 (M)	100	2100	900	1300	945	OPEN TYPE
FE88 I1-S						100	2260	1000	1420	1280	SOUNDPROOF
FE110 I1-O	100	110	114	125	N45TM2A (M)	100	2100	900	1300	1060	OPEN TYPE
FE110 I1-S						140	2850	1000	1420	1525	SOUNDPROOF
FE135 I1-O	120	132	135	148	N45TM3 (M)	100	2100	900	1300	1135	OPEN TYPE
FE135 I1-S						140	2850	1000	1420	1580	SOUNDPROOF
FE140 I1-O	125	138	150	165	N67SM1 (M)	125	2500	1100	1400	1380	OPEN TYPE
FE140 I1-S						160	3000	1100	1520	1720	SOUNDPROOF
FE145 I1-O	130	143	150	165	N67TM2A (M)	125	2500	1000	1400	1345	OPEN TYPE
FE145 I1-S						160	3000	1100	1520	1875	SOUNDPROOF
FE165 I1-O	150	165	178	196	N67TM3A (M)	125	2500	1000	1400	1350	OPEN TYPE
FE165 I1-S						170	3300	1100	1770	1900	SOUNDPROOF
FE165 I1-O			180	198	N67TM4 (M)	125	2500	1000	1400	1350	OPEN TYPE
FE165 I1-S						170	3300	1100	1770	1855	SOUNDPROOF
FE176 I1-O	160	176	178	196	N67TM3A (M)	125	2500	1000	1400	1450	OPEN TYPE
FE176 -IS						170	3300	1100	1770	2060	SOUNDPROOF
FE176 I1-O	160	176	/	/	N67TM4 (M)	125	2500	1000	1400	1450	OPEN TYPE
FE176 I1-S						170	3300	1100	1770	1870	SOUNDPROOF
FE190 I1-O	170	187	200	220	N67TM4 (M)	125	2500	1000	1400	1450	OPEN TYPE
FE190 I1-S						170	3300	1100	1770	2090	SOUNDPROOF
FE220 I1-O	200	220	/	/	N67TM7 (M)	140	2850	1000	1500	1500	OPEN TYPE
FE220 I1-S						170	3300	1100	1770	2100	SOUNDPROOF
FE280 I1-O	250	275	292	320	CURSOR 87 TE3	150	3000	1100	2100	1700	OPEN TYPE
FE280 I1-SB					(E)	220	3800	1200	1940	3300	SOUNDPROOF
FE280 I1-O			270	297	N67TE8P	140	2850	1000	1500	1800	OPEN TYPE
FE280 I1-S					(E)	170	3300	1100	1770	2400	SOUNDPROOF
FE330 I1-O	300	330	358	390	CURSOR 87	150	3000	1100	1850	2550	OPEN TYPE
FE330 I1-SB					TE4 (E)	220	3800	1200	1940	3150	SOUNDPROOF
FE330 I1-O	300	330	333	366	CURSOR 10	150	3000	1100	1850	2550	OPEN TYPE
FE330 I1-SB					TE1D (E)	220	3800	1200	1940	3550	SOUNDPROOF
FE385 I1-O	350	385	385	423	CURSOR 13TE2A	188	3300	1100	2100	2970	OPEN TYPE
FE385 I1-S					(E)	230	3950	1300	2135	3660	SOUNDPROOF
FE440 I1-O	400	440	430	472	CURSOR 13TE3A	320	3400	1400	2200	2900	OPEN TYPE
FE440 I1-S					(E)	230	3950	1300	2135	3700	SOUNDPROOF
FE505 I1-O	450	495	475	540	C13 TE6W (E)	320	3400	1400	2200	3130	OPEN TYPE
FE505 I1-S						260	4500	1450	2190	4340	SOUNDPROOF
FE560 I1-O	500	550	510	565	C13 TE7W (E)	320	3400	1400	2200	3190	OPEN TYPE
FE560 I1-S						260	4500	1450	2190	4430	SOUNDPROOF
FE610 I1-O	550	605	620	690	CR16 TE1W (E)	340	3400	1400	2200	3500	OPEN TYPE
FE610 I1-S						260	4500	1450	2190	4700	SOUNDPROOF
FE630 I1-O	570	630	/	/	CR16 TE1W (E)	340	3400	1400	2200	3500	OPEN TYPE
FE630 I1-S						260	4500	1450	2190	4700	SOUNDPROOF
FE660 I1-O	600	660	/	/	CR16 TE1W (E)	340	3400	1400	2200	3600	OPEN TYPE
FE660 I1-S						260	4500	1450	2190	4800	SOUNDPROOF